FIG. 1



FIG. 2



FIG. 3

Device Descriptor

Offset	Field	Size	Value	Description
0	bLength	1	0x12	Description Length
1	bDescriptionType	1	0x01	Device Descriptor
2	bcdUSB	2	0x0110	USB1.1 compllance
4	bDeviceClass	1	0x00	Intreface specifies the class
5	bDeviceSubClass	1	0x00	
6	bDeviceProtocol	1	0x00	
7	bMaxPaketSize0	1	0x40	64 bytes
8	idVendor	2	0xXXXX	Vender ID
10	idProduct	2	0x0750	Product ID
12	bcdDevice	2	0xXXXX	Device release number
14	iManufacturer	1	0x01	Index of Mfgr strings
15	iproduct	1	0x02	Index of Product strings
16	iSerialNumber	1	0x03	Index of Serial Number strings
17	bNumConfigurations	1	0x01	Single configuration is configurable

Interface Descriptor

Offset	Field	Size	Value	Description
0	bLength	1	0x09	Description Length
1	bDescriptionType	1	0x04	Interface Descriptor
2	bInterfaceNumber	1	0x01	Single interface is configurable
3	bAlfernateSetting	1	0x02	Two Alternate Settings are availlable
4	bNumEndpoints	1	0x03	Three endpoints are Used
5	binterfaceClass	1	0x08	Storage Class
6	binterfaceSubClass	1	0x02	SFF-8020i command is used
7	bInterfaceProtocol	1	0x00	CBI protocol with command interrupt
8	IInterface	1	0x05	Index value of interface strings

FIG. 4

Device Descriptor

Offset	Field	Size	Value	Description
0	bLength	1	0x12	Description Length
1	bDescriptionType	1	0x01	Device Descriptor
2	bcdUSB	2	0x0110	USB1.1 compliance
4	bDeviceClass	1	0x00	Intreface specifies the class
5	bDeviceSubClass	1	0x00	
6	bDeviceProtocol	1	0x00	
7	bMaxPaketSize0	1	0x40	64 bytes
8	idVendor	2	0xXXXX	Vender ID
10	idProduct	2	0x0751	Product ID
12	bcdDevice	2	0xXXXX	Device release number
14	iManufacturer	1	0x01	Index of Mfgr strings
15	iproduct	1	0x02	Index of Product strings
16	iSerialNumber	1	0x03	Index of Serial Number strings
17	bNumConfigurations	1	0x01	Single configuration is configurable

Interface Descriptor

Offset	Field	Size	Value	Description
0	bLength	1	0x09	Description Length
1	bDescriptionType	1	0x04	Interface Descriptor
2	bInterfaceNumber	1	0x01	Single interface is configurable
3	bAlfernateSetting	1	0x03	Three Alternate Settings are availlable
4	bNumEndpoints	1	0x03	Three endpoints are Used
5	binterfaceClass	1	0x06	Still Image Class
6	binterfaceSubClass	1	0x01	Still Image Caputure Device
7	bInterfaceProtocol	1	0x01	PIMA 15740 compliant
8	IInterface	1	0x05	Index value of interface strings

FIG. 5

File Namu	Ext	Attribute	Time	Date	FAT#	File Size
autorun	Inf	0x21	0xXXXX	0xXXXX	0x0002	43
setup	exe	0x21	0xXXXX	0xXXXX	0x0003	365123
setup	ico	0x21	0xXXXX	0xXXXX	0x02DC	2238
XXXXXXXX	XXX	0xXX	0xXXXX	0xXXXX	0xXXXX	XXXX

FIG. 6

```
[ autorun ]
OPEN = SETUP.EXE
ICON = SETUP.ICO
```

FIG. 7

CASE	BANK (1) STATUS	BANK (2) STATUS
1	READ	READ
2	READ	READ DEVICE ID
3	READ	WRITE
4	READ	ERASE BY FLASHING
5	READ DEVICE ID	READ
6	WRITE	READ
7	ERASE BY FLASHING	READ

FIG. 8


START
READ USER MODE SETTING
S101
INSTALLATION IN PERSONAL COMPUTER SELECTED?
NO
S102
YES
PREPARE TO SET PC PROGRAM AREA IN CD-ROM
S103
S104
CONNECTOR TURNED ON?
NO
YES
S105
TIMEOUT?
NO
YES
S106
RESET TO STILL IMAGE
S107
CONNECTOR TURNED OFF?
YES
NO
S108
POWER TURNED OFF?
YES
NO
S109
TIMEOUT
YES
NO
S113
S115
S110
CONNECTION TRANSISTOR OFF?
CHANGE TO STILL IMAGE CLASS MODE
CHANGE TO STILL IMAGE CLASS MODE
S111
CHANGE TO STILL IMAGE CLASS MODE
TURN OFF POWER
S114
S112
CONNECTION TRANSISTOR ON?
END

FIG. 9



FIG. 10 (a)



FIG. 10 (b)



FIG. 11



FIG. 12


START
TAKE IMAGES
S301
RECORD IN BUILT -IN MEMORY?
S302
YES
NO
ENOUGH IMAGE RECORDING CAPACITY REMAINED ?
S304
NO
YES
SEARCH IMAGES HAVING OLDER SHOOTING DATES
S306
IMAGES OF AN IDENTICAL SHOOTING DATE
S307
YES
NO
COMPARE PLAYBACK COUNT
S308
IMAGES OF AN IDENTICAL COUNT?
S309
NO
YES
SEARCH IMAGES HAVING OLDER SHOOTING TIME STAMP
S310
REMOVE SELECTED IMAGES
S311
S305
RECORD IMAGES IN BUILT-IN MEMORY
S303
RECORD IMAGES IN MEMORY CARD
END

FIG. 13



FIG. 14